Subpart L -- United States Standards for Triticale

Terms Defined

§ 810.2001 Definition of triticale.

Grain that, before the removal of dockage, consists of 50 percent or more of triticale (*X Triticosecale* Wittmack) and not more than 10 percent of other grains for which standards have been established under the United States Grain Standards Act and that, after the removal of dockage, contains 50 percent or more of whole triticale.

§ 810.2002 Definition of other terms.

- (a) *Damaged kernels*. Kernels, pieces of triticale kernels, and other grains that are badly ground-damaged, badly weather-damaged, diseased, frost-damaged, germ-damaged, heat-damaged, insect-bored, mold-damaged, sprout-damaged, or otherwise materially damaged.
- (b) *Defects*. Damaged kernels, foreign material, and shrunken and broken kernels. The sum of these three factors may not exceed the limit for the factor defects for each numerical grade.
- (c) *Dockage*. All matter other than triticale that can be removed from the original sample by use of an approved device according to procedures prescribed in FGIS instructions. Also, underdeveloped, shriveled, and small pieces of triticale kernels removed in properly separating the material other than triticale and that cannot be recovered by properly rescreening or recleaning.
- (d) Foreign material. All matter other than triticale.
- (e) *Heat-damaged kernels*. Kernels, pieces of triticale kernels, and other grains that are materially discolored and damaged by heat.
- (f) *Other grains*. Barley, corn, cultivated buckwheat, einkorn, emmer, flaxseed, guar, hull-less barley, nongrain sorghum, oats, Polish wheat, popcorn, poulard wheat, rice, rye, safflower, sorghum, soybeans, spelt, sunflower seed, sweet corn, wheat, and wild oats.
- (g) Shrunken and broken kernels. All matter that passes through a 0.064 x 3/8 oblonghole sieve after sieving according to procedures prescribed in FGIS instructions.
- (h) Sieve. 0.064 x 3/8 oblong-hole sieve. A metal sieve 0.032 inch thick with oblong perforations 0.064 inch by 0.375 (3/8) inch.

Triticale

Principles Governing the Application of Standards

§ 810.2003 Basis of determination.

Each determination of heat-damaged kernels, damaged kernels, material other than wheat or rye, and foreign material (total) is made on the basis of the grain when free from dockage and shrunken and broken kernels. Other determinations not specifically provided for under the general provisions are made on the basis of the grain when free from dockage except the determination of odor is made on either the basis of the grain as a whole or the grain when free from dockage.

Grades and Grade Requirements

§ 810.2004 Grades and grade requirements for triticale.

		Minimum limits of					
		Damaged kernels		Foreign material			
	Minimum			Material		Shrunken	
Grade	test weight	Heat		other than		and broken	
	per bushel	damaged	Total 1/	wheat or rye	Total ^{2/}	kernels	Defects 3/
	(pounds)	(percent)	(percent)	(percent)	(percent)	(percent)	(percent)
U.S. No. 1	48.0	0.2	2.0	1.0	2.0	5.0	5.0
U.S. No. 2	45.0	0.2	4.0	2.0	4.0	8.0	8.0
U.S. No. 3	43.0	0.5	8.0	3.0	7.0	12.0	12.0
U.S. No. 4	41.0	3.0	15.0	4.0	10.0	20.0	20.0

U.S. Sample grade --

- U.Sample grade is triticale that:
- (a) Does not meet the requirements for the grades U.S. Nos. 1, 2, 3, or 4; or
- (b) Contains 8 or more stones or any number of stones which have an aggregate weight in excess of 0.2 percent of the sample weight, 2 or more pieces of glass, 3 or more crotalaria seeds (*Crotalaria* spp.), 2 or more castor beans (*Ricinus communis* L.), 4 or more particles of an unknown foreign substance(s) or a commonly recognized harmful or toxic substance(s), 2 or more rodent pellets, bird droppings, or equivalent quantity of other animal filth per 1-1/8 to 1-1/4 quarts of triticale; or
- (c) Has a musty, sour, or commercially objectionable foreign odor (except smut or garlic odor); or
- (d) Is heating or otherwise of distinctly low quality.

 $[\]frac{1}{2}$ Includes heat-damaged kernels.

 $[\]frac{2}{2}$ Includes material other than wheat or rye.

^{3/2} Defects include damaged kernels (total), foreign material (total), and shrunken and broken kernels. The sum of these three factors may not exceed the limit for defects for each numerical grade.

Special Grades and Special Grade Requirements

§ 810.2005 Special grades and special grade requirements.

- (a) Ergoty triticale. Triticale that contains more than 0.10 percent of ergot.
- (b) *Garlicky triticale*. Triticale that contains in a 1,000-gram portion more than six green garlic bulblets or an equivalent quantity of dry or partly dry bulblets.
- (c) *Light garlicky triticale*. Triticale that contains in a 1,000-gram portion two or more, but not more than six, green garlic bulblets or an equivalent quantity of dry or partly dry bulblets.
- (d) *Light smutty triticale*. Triticale that has an unmistakable odor of smut, or that contains in a 250-gram portion smut balls, portions of smut balls, or spores of smut in excess of a quantity equal to 14 smut balls but not in excess of a quantity equal to 30 smut balls of average size.
- (e) *Smutty triticale*. Triticale that contains in a 250-gram portion smut balls, portions of smut balls, or spores of smut in excess of a quantity equal to 30 smut balls of average size.